AIRMASTER

AM 1000 HH -CP,PHS,ICO,RC - RC TT WCS

Series:
AM

Type:
1000

Version:
1. Characters:
HH – Horizontal Exhaust/Horizontal Supply

HV – Horizontal Exhaust/Vertical Supply

VV –Vertical Exhaust/Vertical Supply

S1S2 – Side Exhaust/Side Supply

Options:

AA	Adaptive Airflow™, automatically adjustable
ADA	Adaptive Airflow™, manually adjustable
ANC	Active Noise Control
BP	Bypass (standard)
CH	Comfort Heater
CP	Condensate Pump
CR	Capacitive Return for ED and SD
ED	Motor-driven Exhaust Air Damper (standard)
EM	Energy Meter
ePM_{10} 50%	Supply air filter ePM_{10} 50%
ePM_1 55%	Supply air filter ePM_1 55%
ePM_1 80%	Supply air filter ePM_1 80% (special part)
PHS	PreHeating Surface
RC	Room cooling module
SD	Motor-driven Supply Air Damper (standard)
WCH	Water Comfort Heater
CO	External CO_2 Sensor
HY	External Hygrostat
ICO	Internal CO_2 Sensor
ICT	Internal CO_2-/TVOC Sensor
IPIR	Internal Motion Sensor
IT	Internal TVOC Sensor
PIR	External Motion Sensor
B1	BACnet™/IP
B2	BACnet™ MS/TP
K	KNX®
L	LON®
M	MODBUS® RTU RS485
AO	Airmaster Airlinq® Online

Version:
TT – Inlet/Extract Top

BB – Inlet/Extract Bottom

TB – Inlet Top/Extract Bottom

BT – Inlet Bottom/ Extract Top

TDE – Inlet Top/ Ducted Extract

BDE – Inlet Bottom/ Ducted Extract

Options, water:
WCS – Water Connection, Side

WCT – Water Connection, Top

Airmaster A/S
Industrivej 59
DK-9600 Aars

Tel.: +45 98 62 48 22
info@airmaster.dk
www.airmaster-as.com

CVR nr.: 29 52 73 93